



CHRISTIE CP2000X

Purpose-built, designed for demanding Digital Cinema applications

Uses

- Cinema/exhibition
- Post-production
- Digital mastering
- Multi-media theatrical productions
- Digital intermediate

Christie's unique split-body design revolutionizes the world of Digital Cinema projection. The separate projection head and ballast lets you put very high power in almost any projection room configuration. The universal ballast gives you maximum flexibility.

Revolutionary design, purpose-built functionality – projection perfection.

Christie CP2000X Specifications


The pinnacle of 3-chip DLP Cinema™ projection technology



Separate, small, variable output ballast has no ripple, reducing flicker – ideal for post-production.



Christie's Touch Panel Controller (TPC™) provides system set-up and control of the projector via the Ethernet, from virtually anywhere.



Christie's LiteLOC™ technology enables constant screen brightness throughout the lifetime of the lamp.

Setting new standards with 2K resolution and up to 21,000 ANSI lumens, the Christie CP2000X delivers spectacular presentations from next-generation DLP Cinema™ technology, high-quality optics and 15-bit image processing. Experience exceptionally crisp and clean images with perfect color saturation in every show.

Offering the ultimate in networkability, on-board ChristieNET™ connectivity lets you control as many units as you want from virtually anywhere.



BRIGHTNESS (MEASURED AT SCREEN CENTER)

- Light output meets 14fL SMPTE recommendation (film 16fL open gate) for screens up to 23m (up to 75ft width)

CONTRAST RATIO

- >2000:1 full field on/off

BRIGHTNESS UNIFORMITY

- >90% when displaying full white screen

TI DLP CINEMA™ TECHNOLOGY

- CineBlack™ Contrast Management
- CineCanvas™ Image Management
- CineLink™ Security Management
- CinePalette™ Color Management

DIGITAL MICROMIRROR DEVICE™

- 2K 3-chip DMD DLP Cinema™
- 2048 x 1080 pixels

INPUT LINE VOLTAGE

- 208V or 400V nominal three-phase at ballast (selectable)
- 200 to 240V single-phase at projection head (less than 10 amps)

COLOR PROCESSING (BIT DEPTH)

- 45-bit (3 x 15-bit resolution)

NUMBER OF COLORS

- 35 trillion

DIGITAL VIDEO INPUT

- Two (2) SMPTE 292M; dual or single

GRAPHICS INPUT

- 2 x DVI interface

POWER SUPPLY

- Separate 7kW low-ripple switch mode lamp ballast

ZOOM LENSES

- 1.25-1.45:1, 1.45-1.8:1, 1.8-2.4:1, 2.2-3.0:1, 3.0-4.3:1, 4.3-6.0:1, 5.5-8.5:1

ANAMORPHIC LENSES (OPTIONAL)

- 1.26:1 (for scope format)

REFLECTOR

- F/1.5 High-Performance Compound Glass Reflector

SAFETY INTERLOCKS

- (4) Lamp Access Door, rear intake vent, extraction port, cable-connected lamp ballast

DOUSER

- Electronic douser

3-AXIS (X, Y + Z) AUTOMATIC LAMP ALIGNMENT

- Christie LampLOC™

AMBIENT TEMPERATURE

- 0 to 35° C (32 to 95° F) (approx)

DIMENSIONS

- Projection head (approx., LxWxH) 48" x 26" x 20"
- Ballast (LxWxH) 21" x 18" x 21"

WEIGHT

- Projection head weight (approx): 260 lbs
- Ballast weight (approx): 110 lbs

DIGITAL PICTURE BY



Corporate Offices

USA
10550 Camden Drive
Cypress, CA 90630
PH: 714-236-8610
FX: 714-503-3385
Toll free: 800-866-4462 (NA only)
sales-us@christiedigital.com

CANADA
809 Wellington Street North
Kitchener, Ontario N2G 4Y7
PH: 519-744-8005
FX: 519-749-3136
Toll free: 800-265-2171 (NA only)
sales-canada@christiedigital.com

Worldwide Offices

UNITED KINGDOM
PH: +44 118 977 8000
FX: +44 118 977 8100
sales-europe@christiedigital.com

GERMANY
PH: +49 2161 664540
FX: +49 2161 664546
sales-europe@christiedigital.com

FRANCE
PH: +33 (0) 1 47 48 28 07
FX: +33 (0) 1 47 48 26 06
Mobile: +33 (0) 6 76 47 43 62
sales-france@christiedigital.com

SINGAPORE
PH: +65 6877 8737
FX: +65 6877 8747
sales-singapore@christiedigital.com

SHANGHAI
PH: +86 21 6278 7708
FX: +86 21 6270 5816
sales-china@christiedigital.com

BEIJING
PH: +86 10 6561 0240
FX: +86 10 6561 0546
sales-china@christiedigital.com

JAPAN
PH: +81 3 3599 7481
FX: +81 3 3599 7482
sales-japan@christiedigital.com

For the most current specification information, please visit www.christiedigital.com

